



HOMECONNECT™

ADSL MODEM DUAL LINK

ADDENDUM 1.1.4

RELEASE NOTES

RESETTING THE MODEM:

If you had a bad install, or wish to reinstall the modem, or if for any reason you need to reset it to its factory configuration, use the following procedure.

1. With the Power cord out, hold in the RESET button on the back of the modem, applying constant pressure. (The RESET button is the small black button next to the console port.)
2. While holding RESET in, plug in the Power cord.
3. Continue to hold in the RESET button for about five seconds. (You can verify that the modem has recognized your instruction as the Alert LEDs will blink rapidly during the RESET procedure.)
4. When the RESET is complete, the LEDs will blink normally. The unit will continue to go through a normal reboot. Once complete, it will have the default configuration.

continued . . .

EXISTING ISSUES:

- 1 In Windows Me, unplugging the USB cable will cause the PC to hang. Don't unplug the cable, even when requested to do so during uninstallation.
- 2 When installing in PPPoA mode certain PCs fail to handle USB cable pulls during data transfer gracefully.
- 3 You have to upgrade to Internet Explorer 4.0 (or Netscape Navigator 4.0) or better to successfully use the Dual Link.
- 4 Netscape 6.0 does not set up file associations properly. This has been verified on Win98. HTML filename extensions have to be manually associated with the new browser executable. If this is not done, Modem Settings and Online Manuals will not work properly.
- 5 During Windows NT installation, you can safely ignore the message "Cannot find RASAPI.DLL . . ."