


# Installation Guide

**Wait!**  
Insert the Dual Link Installation CD in your CD-ROM Drive and follow along with this step-by-step guide.



## HOMECONNECT® ADSL Modem Dual Link Installation Guide

**1** Congratulations on your purchase of the 3Com HomeConnect ADSL Modem Dual Link.

Unpack your kit and insert the Dual Link Installation CD in your CD-ROM drive. DO NOT connect any cables yet. You should cable your modem as directed during the install process.



**2** The CD should autoplay and display the following screen.

If the CD does not autoplay, select **start>run** and type **D:\setup.exe** where **D:** is the letter of your CD-ROM drive.



**3** When this screen appears, connect one end of the DSL cable (supplied) to the DSL wall jack and the other end to the ADSL port on the back of your modem, then click **Next**.




**4** Connect the power cable to the back of your modem and to the power plug.



Wait for the Alert light on the front of the modem to stop flashing, then click **Next**.



**5** When this screen appears, select how you will connect your PC to the Dual Link modem, then click **Next**.



**6** **USB Cabling**

When this screen appears, connect the flat end of the USB cable to your PC and the other end to your modem.


**Follow USB Steps One to Four to complete the USB Installation.**




When this screen appears, connect one end of your Ethernet cable to the Ethernet port on your PC and the other end of the Ethernet cable to the LAN port on the Dual Link, then click **Next**.

### Ethernet Cabling

**The LAN light on the front of the modem should turn GREEN.**



**USB-1** Click **Next** through the following screens. (Note: Windows 2000 install screens will vary slightly from those shown. Simply continue through to the end of the procedure.)



**USB-2** If this message is displayed, insert your Windows '98 CD-ROM and click **OK**.




**USB-3** When this screen appears (it could take up to one minute) make sure the Dual Link Installation disk is in the CD-ROM drive, then click **Finish**.




**USB-4** If this screen appears, click **Yes** to restart your PC.


It could take up to three minutes for your PC to restart. When your PC restarts, the Dual Link installation will automatically continue at step 7. (Note: In Windows 2000, the USB Cabling screen will redisplay with an active **Next** button. Click **Next** to continue.)



**7** The following screen will appear when a continuity check of cabling and driver installation is complete. If the check was successful, click **Next**. Otherwise, click **Help**.



**8** When this screen appears, select your Internet Service Provider (ISP) from the selection boxes, then click **Next**.



Depending on what you select, you may see one or more of the following screens. Complete the required information, then click **Next**.



**9** The setup procedure will now copy files to your system.



After clicking **Next** you may be directed to insert your Windows CD and restart your computer. Follow the directions on the screen.

**10** The following screen may vary slightly from what is shown here, depending on the information you input about your service provider. It will tell you what your next steps are to fully begin accessing the Internet.

